



PO Box 1133, Gray, ME 04039 866.345.WiFi (866.345.9434)



CheckBox HSV510 Specifications & Features

Release 4.29 and up

The CheckBox HSV510 is a completely self-contained, stand alone guest Internet solution, ideal for motels, hotels, marinas, resorts, school campuses, apartment and condominium communities and more. The HSV510 supports 4 high speed Internet connections with automatic failover and does not require a dedicated computer.

All CheckBox HSV510 systems Feature:

- Captive portal - no WEP or WPA required
- Supports wired and wireless clients
- Splash page and redirect page fully configurable - no vendor banner ads or logos required
- Splash page can be location or region specific
- Splash page can be dynamically updated with your current CMS (content management system)
- Domain White List - allow access to pre-specified domains without validation
- Multiple validation options - tickets, limited or unlimited free access, credit cards & Perma codes
- Property Management Integration - Supports integration with Property Management Systems
- Participant loyalty/rewards program capable with provided API

- VPN support for end clients for connecting to corporate clients
- Single SSID throughout system, supports roaming among AP's
- Compatible with all Operating Systems - No configuration changes required on guest laptops
- UPnP supported
- Support for static IP clients
- Supports self-correcting mesh architecture with redundant connections between nodes
- Self-configuring architecture supports wireless & wired mesh nodes for rapid, low cost deployment

- Client-to-Client security isolation supported
- Bandwidth throttling and management
- Torrent inhibiting control
- Supports up to 4 Internet connections standard with load sharing and automatic failover for redundancy
- System firewall to protect guests from external threats
- Tunneling VPN for easy management without port forwarding, static IP's, or manual DMZ settings
- Easily operates outside of corporate telecommunication infrastructure for PCI compliance
- Can be used with external content filtering services
- Web based administrative tools
- Remote access for off-site property management
- 24/7 monitoring with text or email notifications of outages
- Automatic software upgrades

- SMTP redirect available
- Live 24/7 Guest Support available

Specifications

Management Web based GUI
 4 gigabit WAN Port
 4 gigabit LAN Ports
 19" 1RU with rack ears
 Power requirements 120VAC
 Operating temp 0 ~ 70.C

www.CheckBoxSystems.net 866.345.9434