



866.345.WiFi (866.345.9434)



CheckBox HSV726 MultiGigabit Controller

Release 4.56 and up

Designed for large venues, or any location with high traffic and bandwidth needs, the HSV726 provides a solid foundation to build your WiFi service on for an outstanding experience for your guests and staff.

The HSV726 features two 10Gb SFP and six Multi-Gig Ethernet ports powered by four cores of processing power connecting to the next generation of high speed Internet service offered by fiber and cable providers and delivers that service to your guests and staff. With up to 8 Gig of system throughput the HSV726 can deliver the streaming, zooming and online experience your guests want and your staff need to work efficiently.

All CheckBox HSV726 Controllers Feature:

- Two 10 Gb SFP ports
- Six 2.5 Gb Ethernet ports
- Up to 8 Gigabits of system throughput
- MultiNet - Up to three wireless networks from one controller and one set of access points
- S/A/F/E – The Survey And Feedback Engine
- Captive portals support multiple, separate guest networks
- Separate encrypted networks for management and property use
- Supports wired and wireless clients
- Splash pages and redirect pages fully configurable - no vendor banner ads or logos required
- Splash pages can be dynamically updated with your CMS (content management system)
- Domain White List - allow access to pre-specified domains without validation
- Multiple validation options - tickets, limited or unlimited free access, credit cards & Perma Codes and API access
- Property Management Integration - Supports integration with Property Management Systems
- Can integrate with loyalty and rewards program with API
- VPN support for users
- Supports roaming among AP's
- Supports self-correcting mesh architecture with redundant connections between nodes
- Self-configuring architecture supports wireless & wired mesh nodes for rapid, low cost deployment
- Client-to-Client security isolation supported
- Bandwidth throttling and management
- Torrent inhibiting control
- Supports up to 7 Internet connections with load sharing and automatic failover for redundancy
- System firewall helps protect users from external threats
- VPN for easy management without port forwarding, static IP's, or manual DMZ settings
- Can easily operate outside of corporate infrastructure for PCI compliance
- Can be used with external content filtering services
- Web based administrative tools
- Remote access for off-site property management
- 24/7 monitoring with text or email notifications of outages
- Automatic software upgrades
- Live 24/7 Guest Support available

Specifications

Web based GUI for management

Two 10Gb SFP ports

Six 2.5Gb Ethernet ports (10/100/1000/2500) (1 dedicated WAN, 1 dedicated LAN, 4 configurable)

19" 1RU with rack ears

Power requirements 120VAC

Operating temp 0 ~ 70.C